

PM 1340GT Threading Configuration

Imperial TPI			Right Gear Lever Position									
			1	2	3	4	5	6	7	8		
Gear Arrangement			Left Gear Lever Position	A	4	4.5	4.75	5	5.5	6	6.5	7
Top Pair	40	127		B	8	9	9.5	10	11	12	13	14
Bottom Pair	127	40		C	16	18	19	20	22	24	26	28
				D	32	36	38	40	44	48	52	56
				E	64	72	76	80	88	96	104	112

PM1340 Metric Threading - as delivered with 120/127 tooth main gear, 30, 32 and 40 tooth smaller gears

David P. Best

January 12, 2020

Metric Pitch	Where Used		Gear Configuration		Gear Box Settings		Metric Pitch
	Metric Coarse	Metric Fine	Upper Pair	Lower Pair	Letter	Number	
0.2		M1.0 to M1.8	30/127	120/32	E	8	0.2
0.25		M2.0 , M2.2	40/127	120/40	E	6	0.25
0.35	M1.6 x 0.35	M2.5 , M3 , 3.5	40/120 **	127/32	E	6	0.35
0.4	M2.0 x 0.4		32/127	120/40	D	6	0.4
0.45	M2.5 x 0.45		30/120 **	127/32	D	8	0.45
0.5	M3 x 0.5	M4 to M5.5	40/127	120/40	D	6	0.5
0.6	M3.5 x 0.6		32/127	120/40	D	1	0.6
0.7	M4 x 0.7		35/127 *	120/30	D	4	0.7
0.75		M6, M7, M8	40/127	120/40	D	1	0.75
0.8	M5 x 0.8		32/127	120/40	C	6	0.8
1	M6 x 1.0	M8 to M11 x 1.0	40/127	120/40	C	6	1
1.25	M8 x 1.25	M10 x 1.25	30/127	120/32	C	2	1.25
1.5	M10 x 1.5		40/127	120/40	C	1	1.5
1.75	M12 x 1.75		35/127 *	120/40	B	6	1.75
2	M14 & M16 x 2.0		40/127	120/40	B	6	2
2.5	M20 & M22 x 2.5		30/127	120/32	B	2	2.5
3	M24 & M 27 x 3		40/127	120/40	B	1	3
3.5	M30 x 3.5		35/127 *	120/40	A	4	3.5
4	M36 x 4		40/127	120/40	A	6	4
4.5	M42 x 4.5		30/127	120/32	A	4	4.5
5	M48 x 5		40/127	120/32	A	6	5
5.5	M56 x 5.5		Not available				5.5
6	M64 & M68 x 6		40/127	120/40	A	1	6

* These threads require a 35 tooth gear from Quality Machine Tools

** Requires inverting 120/127 Gear If which may require spacer or bushing to ensure clearance and proper alignment with smaller threading gears.

Coarse Metric Thread Pitches				
Size - Nominal Diameter (mm)	Pitch ¹⁾ (mm)	Clearance Drill (mm)	Tap Drill (mm)	Size - Nominal Diameter (mm)
M 1.0	0.25	1.2	0.75	M 1.0
M 1.1	0.25	1.3	0.85	M 1.1
M 1.2	0.25	1.4	0.95	M 1.2
M 1.4	0.3	1.6	1.1	M 1.4
M 1.60	0.35	1.8	1.25	M 1.60
M 2.00	0.4	2.4	1.6	M 2.00
M 2.50	0.45	2.9	2	M 2.50
M 3.00	0.5	3.4	2.5	M 3.00
M 3.50	0.6	3.9	2.9	M 3.50
M 4.00	0.7	4.5	3.3	M 4.00
M 4.5	0.75	5	3.7	M 4.5
M 5.00	0.8	5.5	4.2	M 5.00
M 6.00	1	6.6	5	M 6.00
M 8.00	1.25	9	6.8	M 8.00
M 10.00	1.5	12	8.5	M 10.00
M 12.00	1.75	14	10.2	M 12.00
M 14.00	2	16	12	M 14.00
M 16.00	2	18	14	M 16.00
M 20.00	2.5	22	17.5	M 20.00
M 22.00	2.5	25	19.5	M 22.00
M 24.00	3	27	21	M 24.00
M 27.00	3	30	24	M 27.00
M 30.00	3.5	33	26.5	M 30.00
M 36.00	4	40	32	M 36.00
M 42.00	4.5	46	37.5	M 42.00
M 48.00	5	53	43	M 48.00
M 56.00	5.5	62	50.5	M 56.00
M 64.00	6	70	58	M 64.00
M 68.00	6	74	62	M 68.00

Fine Metric Thread Pitches					
Size - Nominal Diameter (mm)	Pitch ¹⁾ (mm)	Tap Drill (mm)	Size - Nominal Diameter (mm)	Pitch ¹⁾ (mm)	Tap Drill (mm)
M 1.0 x 0.2	0.2	0.8	M 12 x 1	1	11.00
M 1.1 x 0.2	0.2	0.9	M 12 x 1.25	1.25	10.80
M 1.2 x 0.2	0.2	1	M 12 x 1.5	1.5	10.50
M 1.4 x 0.2	0.2	1.2	M 14 x 1.0	1	13.00
M 1.6 x 0.2	0.2	1.4	M 14 x 1.25	1.25	12.80
M 1.8 x 0.2	0.2	1.6	M 14 x 1.5	1.5	12.50
M 2 x 0.25	0.25	1.75	M 12 x 1.5	1.5	10.50
M 2.2 x 0.25	0.25	1.95	M 14 x 1.0	1	13.00
M 2.5 x 0.35	0.35	2.1	M 14 x 1.25	1.25	12.80
M 3 x 0.35	0.35	2.6	M 14 x 1.5	1.5	12.50
M 3.5 x 0.35	0.35	3.1	M 15 x 1	1	14.00
M 4 x 0.35	0.35	3.6	M 15 x 1.5	1.5	13.50
M 4 x 0.5	0.5	3.5	M 16 x 1	1	15.00
M 4.5 x 0.5	0.5	4	M 16 x 1.5	1.5	14.50
M 5 x 0.5	0.5	4.5	M 17 x 1.0	1	16.00
M 5.5 x 0.5	0.5	5	M 17 x 1.5	1.5	15.50
M 6 x 0.75	0.75	5.2	M 18 x 1.0	1	17.00
M 7 x 0.75	0.75	6.2	M 18 x 1.5	1.5	16.50
M 8 x 0.5	0.5	7.5	M 18 x 2.0	2	16.00
M 8 x 0.75	0.75	7.2	M 20 x 1.0	1	19.00
M 8 x 1.0	1	7	M 20 x 1.5	1.5	18.50
M 9 x 0.75	0.75	8.2	M 20 x 2.0	2	18.00
M 9 x 1	1	8	M 22 x 1.0	1	21.00
M 10 x 0.75	0.75	9.2	M 22 x 1.5	1.5	20.50
M 10 x 1	1	9	M 22 x 2.0	2	20.00
M 10 x 1.25	1.25	8.8	M 24 x 1.0	1	23.00
M 11 x 0.75	0.75	10.2	M 24 x 1.5	1.5	22.50
M 11 x 0.75	0.75	10.2	M 24 x 2.0	2	22.00
M 11 x 1	1	10	M 25 x 1.0	1	24.00
			M 25 x 1.5	1.5	23.50
			M 25 x 2.0	2	23.00